

TORQUE SPECIFICATION

Part tightened	N·m	kgf·cm	ft·lbf
Fuel line for union bolt for flare nut (for using SST)	29 38 (30)	300 387 (310)	22 28 (22)
Fuel tank vent tube set plate x Fuel tank	4.0	40	35 in·lbf
Fuel inlet hose x Body	9.0	90	80 in·lbf
Delivery pipe x Cylinder head	18.5	185	13
Air cleaner assembly x Intake manifold	7.5	75	65 in·lbf
Air cleaner assembly x Air cleaner inlet duct bracket	7.5	75	65 in·lbf
Air cleaner inlet x Radiator fan shroud	5	5.0	43 in·lbf
Fuel pressure pulsation damper x No.1 fuel pipe (for using SST)	32 (27)	320 (270)	23 (20)
Throttle position sensor x Throttle body	2.0	20	17 in·lbf
Throttle control motor x Throttle body	3.7	37.5	33 in·lbf
Throttle body x Intake manifold	21	210	15
Throttle body x VSV and bracket assembly	7.5	75	66 in·lbf
Intake manifold x VSV and bracket assembly	7.5	75	66 in·lbf
Accelerator pedal position sensor x Throttle pedal position housing	2.0	20	17 in·lbf
Accelerator pedal position housing x Throttle body	5.4	55	48 in·lbf
Camshaft timing oil control valve x No.1 camshaft bearing cap	8.0	80	71 in·lbf
No.2 cylinder head cover x Air cleaner inlet duct bracket	6.5	65	56 in·lbf
No.2 cylinder head cover x No.1 camshaft bearing cap	8.5	85	74 in·lbf
Water temperature sensor x Cylinder head	19.6	200	14
Knock sensor x Cylinder block	45	450	33
Oxygen sensor x Exhaust manifold	44	450	32
Oxygen sensor x Center exhaust pipe	44	450	32