

TORQUE SPECIFICATION

Part tightened	N·m	kgf·cm	ft·lbf
Master cylinder x Brake booster	13	130	9
Master cylinder x Piston stopper bolt	10	102	7
Brake line union nut	15	155	11
Brake booster clevis lock nut	25	260	19
Brake booster x Pedal bracket	13	130	9
Bleeder plug (Brake caliper)	11	110	8
Bleeder plug (ABS & TRC actuator)	8.3	85	74 in.·lbf
Brake pedal x pedal bracket	39	400	29
Reservoir set screw	1.8	18	16 in.·lbf
Front brake caliper installation bolt	34	350	25
Front disc brake caliper x Flexible hose	30	310	22
Front disc brake torque plate x Steering knuckle	118	1,200	87
Rear disc brake caliper x Flexible hose	30	310	22
Rear disc brake caliper x Rear axle carrier	104	1,065	77
ABS & TRC Actuator x Actuator Bracket	5.4	55	48 in.·lbf
ABS & TRC Actuator Assembly x Body	19	195	14
Front speed sensor installation bolt	8.0	82	71 in.·lbf
Front speed sensor harness clamp bolt	5.0	51	44 in.·lbf
Rear speed sensor installation bolt	8.0	82	71 in.·lbf
Rear speed sensor harness x Body	5.0	51	44 in.·lbf
Rear speed sensor harness x Toe control link	5.0	51	44 in.·lbf